

COMMERCIAL REFRIGERATION EQUIPMENT TECHNICAL INFORMATION AND SPECIFICATIONS

WORKTOPS REFRIGERATORS, FREEZERS & BACKBARS





Point mobile device to view & save contact details

Supercold Refrigeration Systems Pvt Ltd

Industrial Estate, Manvila, Kulathur
THIRUVANANTHAPURAM – 695583, KERALA, INDIA
(0471)2595339, 9745333522, 9745333711, FAX: 2598436
info@supercoldindia.com sales@supercoldindia.com
www.supercoldindia.com



Supercold No-Frost Worktop Freezers & Chillers 304 Food Grade Stainless Steel Cabinet

Worktop Refrigerators are designed to take care of the two biggest problem faced by busy commercial kitchens. Lack of Storage Space & Lack of Work Space. Worktops are basically refrigerated storage units which double up as an extra work table for your kitchen on a space which would have otherwise gone to waste.

Front Breathing Condenser Design ensures the machine can be installed just about anywhere in any kitchen layout. Freezing or Chilling process is quick due to cyclonic circulation of very cold and dry air. Temperature controller with LED display, Energy efficient compressors, automatic condensate disposal (no plumbing needed), LED lighting, self closing and lockable Solid Doors, stainless steel shelves, castor wheels with brakes etc.. are few of the many great standard features across all models. These machines are built to work efficiently and effortlessly, minimizing equipment downtime while letting you concentrate on your core business.

These units are available with a wide range of customization to suit your needs. These can range from refrigerated Misé En Place Counters, Ambient / Heated Pickup Shelves (Quartz Heaters), Back / Side Splash, Pullout Drawers instead of swing doors, double / triple pane glass doors etc.. based on your needs.



SPECIFICATIONS FOR COMMERCIAL UNDER COUNTER REFRIGERATORS									
REGULAR MODELS	VOLUME IN LITERS	650ml BEER BOTTLES - Nos	CONNECTED LOAD IN WATTS	CURRENT	REFRIGERANT	VOLTAGE STABILISER CAPACITY - KVA	OVERALL DIMENSION IN cms WDH	DOORS	SHELF
WT 500 SS	482	252	550	5.9	134a	2 KVA	180x70x90	3	3
WT 350 SS	320	160	475	2.7	134a	1 KVA	132x70x90	2	2



Supercold no frost Back Bar Chiller at 2° to 7°C.



Back Bar Chillers are a great addition to your Bar Counter. They easily fit under your counter while offering maximum user convenience and storage space for your drinks. These units come with front breathing condenser design which makes sure the machine can be fitted in just about any layout without affecting air flow path to the condenser for cooling. These units can be custom made and are also available without the condenser panel visible from the front of the unit.

SPECIFICATIONS FOR COMMERCIAL BACK BAR REFRIGERATORS									
REGULAR	VOLUME IN LITERS	650ml BEER BOTTLES - Nos	CONNECTED LOAD IN WATTS	CURRENT	REFRIGERANT	VOLTAGE STABILISER CAPACITY - KVA	OVERALL DIMENSION IN cms WDH	DOORS	SHELF
BB 500	482	252	675	5.9	134a	2 KVA	180x70x90	3	3
BB 350	320	160	500	2.7	134a	1 KVA	132x70x90	2	2





1 / 2 / 3 / 4 DOOR WORKTOP REFRIGERATORS & FREEZERS



Features & Specifications						
Dimension	84(W) X 70(D) X 80+15(H)mm – 170 Ltrs (1 Door) 132(W) X 70(D) X 80+15(H)mm – 340 Ltrs (2 Doors) 180(W) X 70(D) X 80+15(H)mm – 512 Ltrs (3 Doors)					
Temperature	-20°C for Freezer, 2 to 8°C for Cooler					
Refrigerant	R404a or R134a					
Temperature Controller	Danfoss make, External, User Adjustable with LED Temperature Display					
Customization	Refrigerated Mise En Place Counters, Back Splash / Side Splash, Pickup Shelves (Plain or Heated), Glass Doors, Pullouts, Overlapping Wide Doors for 50 X 70 Pastry Trays etc					
Cooling Method	Side Mounted No-Frost Cyclonic™ Refrigeration System. Front Breathing Design Condensatio Unit with perforated base to ensure optimum air flow to condenser for even the most cramped commercial kitchens. Tool Free Access to all serviceable areas.					
Defrost	Heater Aided, Timer Activated, Frost Sensed					
Condensate Disposal	Automatic, Hot Refrigerant Bypass Aided, (No water tray which requires frequent emptying)					
Inner Cabinet Width	Suitable for up to GN Pan Size 1/1 (530mm X 325mm)					
Material	Fully Body in 304 Grade SS including Doors, Shelves & Railings					
Doors	Lockable Auto-closing Imported Spring Loaded Doors with recessed Handles. Soft Snap Fit Gaskets for easy removal / cleaning, Switches to switch off Fan & switch on Lights when door are opened. Optional Triple Pane Glass Doors (SS 304 Frame) for Chillers.					
Cabinet Lighting	Hidden LED Tube in Recessed Cavity					
Condensation	Oversized Condenser with Powerful Axial Fan for high efficiency in peak summers					
Legs	15 Cm High, Height Adjustable, 304 Grade, Wheels are optional					
Voltage Protection	Inbuilt High/Low Voltage Cutoff (170VAC to 255VAC)					

Supercold Refrigeration Systems Pvt Ltd Industrial Estate, Manvila, Kulathur THIRUVANANTHAPURAM – 695583, KERALA, INDIA (0471)2595339, 9745333522, 9745333711, FAX: 2598436 info@supercoldindia.com sales@supercoldindia.com www.supercoldindia.com